# Masai Cables

# Building Stronger Connections.



# **PRODUCT CATALOGUE**

#### **Building Stronger Connections**

#### **DOMESTIC CABLE**

Single Core Size : 1.0 - 630 sq.mm



#### · 450/750 V

- Fire Retardant Low Smoke (FRLS)
- Single core cables

• Stranded annealed copper conductors •Used for domestic house wiring

•KS EAS 114

#### SUBMERSIBLE CABLES

3 & 4 Core Size : 1.5 - 35 sq.mm



#### .600/1000 V

•Multicore flat or round flexible submersible cable

- •PVC insulated
- •Light Blue
- KS IEC 60502-1

#### CONCENTRIC NEUTRAL CABLE (CNC) **Single Phase Cable**

Size : 10 - 35 sq.mm



#### .600/1000 V

• PVC or XLPE Insulated concentric cable with Aluminium or copper conductors.

#### TWIN DOMESTIC CABLE

**Twin Flat & With Earth** Size : 1.0 - 16 sq.mm



#### · 300/500 V

• PVC insulated Black and Red, with Grey oversheath

- •Available in stranded & solid conductors
- •Used for power extension for


connecting domestic appliances • KS EAS 114

#### WELDING CABLE

Size : 10 - 630 sq.mm

#### FLEXIBLE CABLES

Multicore Size : 0.5 - 50 sq.mm



#### · 450/750 V

• PVC insulated, Multicore with flexible conductors Oversheath black or white •Used for conecting domestic appliances & wiring of control panels • KS EAS 117

#### **BARE ALL ALLUMINIUM** CONDUCTOR (AAC)

Size : 10 - 150 sq.mm

• Aluminium wires with circular strands

- · Bare, round, stranded and compacted.
- BS 215-2

#### **ARMOURED CABLE**

Single Core (Al / Cu) Size : 50 - 630 sq.mm

Multicore Size (Cu) : 1.5 - 400sq.mm Size (Al) : 10 - 400sq.mm



#### .600/1000 V

- PVC or XLPE insulated black and red
- •Steel wire armour with PVC black
- KS IEC 60502-1

#### NON ARMOURED CABLE

**Multicore Single Core** Size : 50 - 630 sq.mm



.600/1000 V • PVC/XLPE insulated Stranded annealed Copper/ Aluminium conductors

• KS IEC 60502-1

- .600/1000 V
- Welding/DC cable
- Flexible cable
- PVC double insulated
- · Orange or black outer cover
- KS 1637

• KS 1022

# PRODUCT CATALOGUE

#### **Building Stronger Connections**

#### ALUMINIUM CONDUCTOR Steel Reinforced

Size : 25 - 150 sq.mm



Aluminium conductors for overhead power transmission
KS IEC 50182

#### AUTOMOTIVE CABLES

Size : 0.5 - 50 sq.mm



PVC covered conductors for automotive wiring
KS 04-314

#### **AERIAL BUNDLED CABLE (ABC)**

**Overhead Cable** Size : 25 - 150 sq.mm



600/1000 V
UV Resistant black XLPE insulated
KS 2650

#### \*\*\*CALL OR WRITE TO US FOR CUSTOMISED CABLE TYPES & SIZES\*\*\*

#### **SPECIALITIES OF MASAI CABLES**

- FIRE RETARDANT LOW SMOKE (FRLS) PVC USED IN DOMESTIC CABLES.
- EC GRADE 99.9% PURE COPPER USED IN ALL COPPER CABLES.
- EC GRADE ALUMINIUM USED IN ALL ALUMINIUM CABLES.
- ALL PROCESSES LIKE WIRE DRAWING FROM RODS, ANNEALING , INSULATING TO PACKING ALL UNDER ONE ROOF.
- MODERN TEST LABORATORY SET UP FOR VARIOUS CRUCIAL TESTS.
- QUALITY CHECKS AT VARIOUS STAGES IN THE MANUFACTURING PROCESS.
- WORKING UNDER ISO 9001 2015 QUALITY MANAGEMENT SYSTEM.
- WIDE VARIETY OF CABLE TYPES FOR ALL YOUR NEEDS INCLUDING CABLES FOR DOMESTIC, INDUSTRIAL, AUTOMOTIVE & POWER TRANSMISSION.
- MULTIPLE SALES OUTLETS FOR FAST & EFFICIENT DELIVERIES.
- AN "EASY TO DO BUSINESS WITH" COMPANY.
- BIG MANUFACTURING CAPACITY OF 160 MT OF COPPER AND 200 MT OF ALUMINIUM CABLES.

## ...BUILDING STRONGER CONNECTIONS...



### Scan QR Code to Visit Website

Masai Cables Limited. P.O.BOX 344 - 00242 T : +254 745 910 871 E : sales.mcl@masaigroup.co.ke Kitengela , Kenya

